





As wool experts since 1888, we create products that offer more than just performance. We're on a journey to use wool as a force for positive change. Through innovation and holistic frameworks, we drive a positive impact in the field by creating market-leading products sourced from verified traceable wool, through our fair price assurance programme, The Woolkeepers®

Standard Product: Nonwoven layers **Applications:** Outerwear, outdoor, sleeping bags, apparel, accessories

HD® Wool Active | Certified traceable natural wool fibres are hand selected and processed to create machine washable performance insulation which keeps skin temperature 3% lower during exercise and manages sweat for 95% longer than synthetic insulation.

Grown in the UK, created within 50miles, built for brands who design with regeneration and circularity in mind.



HD® Wool Apparel Insulation Ltd, Salts Mill, First Floor, Shipley, West Yorkshire, England, BD18 3LA, Company Registration Number: 12040789 info@hdwool.com | +44 (0) 1274 769123



Features:

- Natural and renewable
- Thermo-regulating
- Breathable
- · Odor inhibiting, anti-bacterial
- · 3rd party verified traceable wool
- Non-mulesed

Care Instructions:

- Wash on wool/gentle cycle 40°C / 104°F
- Use wool detergent
- Dry flat
- Do not iron



Due to manufacture processes and natural fibre content other properties may vary

				THE	PERTIES	
INSULATION WEIGHT	PRODUCT CODE	ROLL LENGTH	THICKNESS BS EN ISO 9073-2	THERMAL RE		MOISTURE VAPOUR RESISTANCE ISO 11092
g/m ² & oz/yd ²			mm / in.	CLO	Rct (m².K/W)	Ret (m².Pa/W)
75 / 2.2	HD75ACT	60m / 65yd	11 / 0.43	0.9 - 1.1	0.16	8 -11
100 / 3.0	HD100ACT	50m / 55yd	11 / 0.43	1.2 - 1.4	0.19	12 - 14
125 / 3.6	HD125ACT	45m / 50yd	13 / 0.51	1.4 - 1.6	0.23	17 - 21
150 / 4.4	HD150ACT	40m / 45yd	15 / 0.59	1.7 - 1.9	0.27	
200 / 5.9	HD200ACT	35m / 40yd	25 / 0.98	2.2 - 2.3	0.34	22 - 27

Test Methods:

Compression Recovery (IHTM 110) | Machine Washable (BS EN ISO 5077) | Tumble Dry Low (BS EN ISO 5077)

Standard Width:

150 cm | 59 inches

Tolerances: Width: -10mm / +30mm | -0.39 inches / +1.18 inches Weight: ±10%